

fit interiors ——— designed and produced in Italy

Collective

DESIGN FIRST.

fit interiors

Index

CANB3W45-23	4	CANB3W40-23	16
CANB4W45-23	5	CANB4W40-23	17
CANB5W45-23	6	CANB5W40-23	18
CANB3W45-24V-23	7	CANB3W40-24V-23	19
CANB4W45-24V-23	8	CANB4W40-24V-23	20
CANB5W45-24V-23	9	CANB5W40-24V-23	21
CANB3W45FR-23	10	CANB3W40FR-23	22
CANB4W45FR-23	11	CANB4W40FR-23	23
CANB5W45FR-23	12	CANB5W40FR-23	24
CANB3W45FR-24V-23	13	CANB3W40FR-24V-23	25
CANB4W45FR-24V-23	14	CANB4W40FR-24V-23	26
CANB5W45FR-24V-23	15	CANB5W40FR-24V-23	27

Numbers	28
Accessories	28
Locks	29
Additions	34
Finishes	38

Collective

Single column locker with doors in transparent polycarbonate.

Options

- Internal structure in two colors: black or white

Door

Polycarbonate




Transparent

Structure

Finishes



Matt black
wax




White wax

Fire retardant structure

Finishes



Matt black
wax



White wax

Included equipment



Keylock



Braked hinges



Number made
of PVC

Key for optionals on request

01 • Numbers
(only adhesive numbers,
replacing standard equipment)


 • Locks
(Excluded: ACCGAT.
Replacing standard equipment)

 • USB socket

Symbols



FIRE RESISTANCE
structure in MFC panels, flammability and
flame retardancy class B-s1, d0 (EN 13501-1)



CANB3W45-23

Single column locker with 3 doors in transparent polycarbonate


- Structure in 18 mm thick MFC panels
- ABS edging with polyurethane glue
- Door in transparent polycarbonate 15 mm thick
- Adjustable feet
- Hinges certified for 80,000 opening and closing cycles
- Braked hinges
- Door opening angle 155°.
- Door number in resin-coated sticker with Fit Interiors logo
- Keylocks (with 2 keys + numbered locker key wrist strap)

Dimensions

W 450 mm / D 547 mm / H 2100 mm
 Height with skirting board 2170 mm

Optional upon request





CANB4W45-23

Single column locker with 4 doors in transparent polycarbonate


- Structure in 18 mm thick MFC panels
- ABS edging with polyurethane glue
- Door in transparent polycarbonate 15 mm thick
- Adjustable feet
- Hinges certified for 80,000 opening and closing cycles
- Braked hinges
- Door opening angle 155°.
- Door number in resin-coated sticker with Fit Interiors logo
- Keylocks (with 2 keys + numbered locker key wrist strap)

Dimensions

W 450 mm / D 547 mm / H 2100 mm
 Height with skirting board 2170 mm

Optional upon request





CANB5W45-23

Single column locker with 5 doors in transparent polycarbonate

- Structure in 18 mm thick MFC panels
- ABS edging with polyurethane glue
- Door in transparent polycarbonate 15 mm thick
- Adjustable feet
- Hinges certified for 80,000 opening and closing cycles
- Braked hinges
- Door opening angle 155°.
- Door number in resin-coated sticker with Fit Interiors logo
- Keylocks (with 2 keys + numbered locker key wrist strap)


Dimensions

W 450 mm / D 547 mm / H 2100 mm

Height with skirting board 2170 mm

Optional upon request





CANB3W45-24V-23

Single column locker with 3 doors in transparent polycarbonate - LED inside

- Structure in 18 mm thick MFC panels
- ABS edging with polyurethane glue
- Door in transparent polycarbonate 15 mm thick
- Adjustable feet
- Hinges certified for 80,000 opening and closing cycles
- Braked hinges
- Door opening angle 155°.
- Door number in resin-coated sticker with Fit Interiors logo
- Keylocks (with 2 keys + numbered locker key wrist strap)
- Trunking LED profile IP20 with power supply

Colour to be chosen among:

(C) 6000 K cold light

(N) 4000 K natural light

(W) 3000 K warm light


Dimensions

W 450 mm / D 547 mm / H 2100 mm

Height with skirting board 2170 mm

Optional upon request





CANB4W45-24V-23

Single column locker with 4 doors in transparent polycarbonate - LED inside

- Structure in 18 mm thick MFC panels
- ABS edging with polyurethane glue
- Door in transparent polycarbonate 15 mm thick
- Adjustable feet
- Hinges certified for 80,000 opening and closing cycles
- Braked hinges
- Door opening angle 155°.
- Door number in resin-coated sticker with Fit Interiors logo
- Keylocks (with 2 keys + numbered locker key wrist strap)
- Trunking LED profile IP20 with power supply

Colour to be chosen among:


- (C) 6000 K cold light
- (N) 4000 K natural light
- (W) 3000 K warm light


Dimensions

W 450 mm / D 547 mm / H 2100 mm

Height with skirting board 2170 mm

Optional upon request





CANB5W45-24V-23

Single column locker with 5 doors in transparent polycarbonate – LED inside

- Structure in 18 mm thick MFC panels
- ABS edging with polyurethane glue
- Door in transparent polycarbonate 15 mm thick
- Adjustable feet
- Hinges certified for 80,000 opening and closing cycles
- Braked hinges
- Door opening angle 155°.
- Door number in resin-coated sticker with Fit Interiors logo
- Keylocks (with 2 keys + numbered locker key wrist strap)
- Trunking LED profile IP20 with power supply

Colour to be chosen among:

(C) 6000 K cold light

(N) 4000 K natural light


(W) 3000 K warm light


Dimensions

W 450 mm / D 547 mm / H 2100 mm

Height with skirting board 2170 mm

Optional upon request





CANB3W45FR-23

Single column locker with 3 doors in transparent polycarbonate


- Structure in 18 mm thick MFC panels
- Flammability and flame retardancy class B-s1, d0 (EN 13501-1)
- ABS edging with polyurethane glue
- Door in transparent polycarbonate 15 mm thick
- Adjustable feet
- Hinges certified for 80,000 opening and closing cycles
- Braked hinges
- Door opening angle 155°.
- Door number in resin-coated sticker with Fit Interiors logo
- Keylocks (with 2 keys + numbered locker key wrist strap)

Dimensions

W 450 mm / D 547 mm / H 2100 mm
 Height with skirting board 2170 mm

Optional upon request





CANB4W45FR-23

Single column locker with 4 doors in transparent polycarbonate


- Structure in 18 mm thick MFC panels
- Flammability and flame retardancy class B-s1, d0 (EN 13501-1)
- ABS edging with polyurethane glue
- Door in transparent polycarbonate 15 mm thick
- Adjustable feet
- Hinges certified for 80,000 opening and closing cycles
- Braked hinges
- Door opening angle 155°.
- Door number in resin-coated sticker with Fit Interiors logo
- Keylocks (with 2 keys + numbered locker key wrist strap)

Dimensions

W 450 mm / D 547 mm / H 2100 mm
 Height with skirting board 2170 mm

Optional upon request





CANB5W45FR-23

Single column locker with 5 doors in transparent polycarbonate


- Structure in 18 mm thick MFC panels
- Flammability and flame retardancy class B-s1, d0 (EN 13501-1)
- ABS edging with polyurethane glue
- Door in transparent polycarbonate 15 mm thick
- Adjustable feet
- Hinges certified for 80,000 opening and closing cycles
- Braked hinges
- Door opening angle 155°.
- Door number in resin-coated sticker with Fit Interiors logo
- Keylocks (with 2 keys + numbered locker key wrist strap)

Dimensions

W 450 mm / D 547 mm / H 2100 mm
 Height with skirting board 2170 mm

Optional upon request





CANB3W45FR-24V-23

Single column locker with 3 doors in transparent polycarbonate - LED inside

- Structure in 18 mm thick MFC panels
- Flammability and flame retardancy class B-s1, d0 (EN 13501-1)
- ABS edging with polyurethane glue
- Door in transparent polycarbonate 15 mm thick
- Adjustable feet
- Hinges certified for 80,000 opening and closing cycles
- Braked hinges
- Door opening angle 155°.
- Door number in resin-coated sticker with Fit Interiors logo
- Keylocks (with 2 keys + numbered locker key wrist strap)
- Trunking LED profile IP20 with power supply

Colour to be chosen among:

(C) 6000 K cold light

(N) 4000 K natural light


(W) 3000 K warm light


Dimensions

W 450 mm / D 547 mm / H 2100 mm

Height with skirting board 2170 mm

Optional upon request





CANB4W45FR-24V-23

Single column locker with 4 doors in transparent polycarbonate - LED inside

- Structure in 18 mm thick MFC panels
- Flammability and flame retardancy class B-s1, do (EN 13501-1)
- ABS edging with polyurethane glue
- Door in transparent polycarbonate 15 mm thick
- Adjustable feet
- Hinges certified for 80,000 opening and closing cycles
- Braked hinges
- Door opening angle 155°.
- Door number in resin-coated sticker with Fit Interiors logo
- Keylocks (with 2 keys + numbered locker key wrist strap)
- Trunking LED profile IP20 with power supply


Colour to be chosen among:


- (C) 6000 K cold light
- (N) 4000 K natural light
- (W) 3000 K warm light

Dimensions

W 450 mm / D 547 mm / H 2100 mm
 Height with skirting board 2170 mm

Optional upon request





CANB5W45FR-24V-23

Single column locker with 5 doors in transparent polycarbonate - LED inside

- Structure in 18 mm thick MFC panels
- Flammability and flame retardancy class B-s1, do (EN 13501-1)
- ABS edging with polyurethane glue
- Door in transparent polycarbonate 15 mm thick
- Adjustable feet
- Hinges certified for 80,000 opening and closing cycles
- Braked hinges
- Door opening angle 155°.
- Door number in resin-coated sticker with Fit Interiors logo
- Keylocks (with 2 keys + numbered locker key wrist strap)
- Trunking LED profile IP20 with power supply

Colour to be chosen among:


- (C) 6000 K cold light
- (N) 4000 K natural light
- (W) 3000 K warm light

Dimensions

W 450 mm / D 547 mm / H 2100 mm
 Height with skirting board 2170 mm

Optional upon request





CANB3W40-23

Single column locker with 3 doors in transparent polycarbonate


- Structure in 18 mm thick MFC panels
- ABS edging with polyurethane glue
- Door in transparent polycarbonate 15 mm thick
- Adjustable feet
- Hinges certified for 80,000 opening and closing cycles
- Braked hinges
- Door opening angle 155°.
- Door number in resin-coated sticker with Fit Interiors logo
- Keylocks (with 2 keys + numbered locker key wrist strap)

Dimensions

W 400 mm / D 547 mm / H 2100 mm
 Height with skirting board 2170 mm

Optional upon request





CANB4W40-23

Single column locker with 4 doors in transparent polycarbonate


- Structure in 18 mm thick MFC panels
- ABS edging with polyurethane glue
- Door in transparent polycarbonate 15 mm thick
- Adjustable feet
- Hinges certified for 80,000 opening and closing cycles
- Braked hinges
- Door opening angle 155°.
- Door number in resin-coated sticker with Fit Interiors logo
- Keylocks (with 2 keys + numbered locker key wrist strap)

Dimensions

W 400 mm / D 547 mm / H 2100 mm
 Height with skirting board 2170 mm

Optional upon request





CANB5W40-23

Single column locker with 5 doors in transparent polycarbonate


- Structure in 18 mm thick MFC panels
- ABS edging with polyurethane glue
- Door in transparent polycarbonate 15 mm thick
- Adjustable feet
- Hinges certified for 80,000 opening and closing cycles
- Braked hinges
- Door opening angle 155°.
- Door number in resin-coated sticker with Fit Interiors logo
- Keylocks (with 2 keys + numbered locker key wrist strap)

Dimensions

W 450 mm / D 547 mm / H 2100 mm
 Height with skirting board 2170 mm

Optional upon request





CANB3W40-24V-23

Single column locker with 3 doors in transparent polycarbonate – LED inside

- Structure in 18 mm thick MFC panels
- ABS edging with polyurethane glue
- Door in transparent polycarbonate 15 mm thick
- Adjustable feet
- Hinges certified for 80,000 opening and closing cycles
- Braked hinges
- Door opening angle 155°.
- Door number in resin-coated sticker with Fit Interiors logo
- Keylocks (with 2 keys + numbered locker key wrist strap)
- Trunking LED profile IP20 with power supply

Colour to be chosen among:

(C) 6000 K cold light

(N) 4000 K natural light


(W) 3000 K warm light


Dimensions

W 400 mm / D 547 mm / H 2100 mm

Height with skirting board 2170 mm

Optional upon request





CANB4W40-24V-23

Single column locker with 4 doors in transparent polycarbonate - LED inside

- Structure in 18 mm thick MFC panels
- ABS edging with polyurethane glue
- Door in transparent polycarbonate 15 mm thick
- Adjustable feet
- Hinges certified for 80,000 opening and closing cycles
- Braked hinges
- Door opening angle 155°.
- Door number in resin-coated sticker with Fit Interiors logo
- Keylocks (with 2 keys + numbered locker key wrist strap)
- Trunking LED profile IP20 with power supply

Colour to be chosen among:

(C) 6000 K cold light

(N) 4000 K natural light

(W) 3000 K warm light


Dimensions

W 400 mm / D 547 mm / H 2100 mm

Height with skirting board 2170 mm

Optional upon request





CANB5W40-24V-23

Single column locker with 5 doors in transparent polycarbonate – LED inside

- Structure in 18 mm thick MFC panels
- ABS edging with polyurethane glue
- Door in transparent polycarbonate 15 mm thick
- Adjustable feet
- Hinges certified for 80,000 opening and closing cycles
- Braked hinges
- Door opening angle 155°.
- Door number in resin-coated sticker with Fit Interiors logo
- Keylocks (with 2 keys + numbered locker key wrist strap)
- Trunking LED profile IP20 with power supply

Colour to be chosen among:

(C) 6000 K cold light

(N) 4000 K natural light

(W) 3000 K warm light


Dimensions

W 400 mm / D 547 mm / H 2100 mm

Height with skirting board 2170 mm

Optional upon request





CANB3W40FR-23

Single column locker with 3 doors in transparent polycarbonate


- Structure in 18 mm thick MFC panels
- Flammability and flame retardancy class B-s1, d0 (EN 13501-1)
- ABS edging with polyurethane glue
- Door in transparent polycarbonate 15 mm thick
- Adjustable feet
- Hinges certified for 80,000 opening and closing cycles
- Braked hinges
- Door opening angle 155°.
- Door number in resin-coated sticker with Fit Interiors logo
- Keylocks (with 2 keys + numbered locker key wrist strap)

Dimensions

W 400 mm / D 547 mm / H 2100 mm
Height with skirting board 2170 mm

Optional upon request





CANB4W40FR-23

Single column locker with 4 doors in transparent polycarbonate


- Structure in 18 mm thick MFC panels
- Flammability and flame retardancy class B-s1, d0 (EN 13501-1)
- ABS edging with polyurethane glue
- Door in transparent polycarbonate 15 mm thick
- Adjustable feet
- Hinges certified for 80,000 opening and closing cycles
- Braked hinges
- Door opening angle 155°.
- Door number in resin-coated sticker with Fit Interiors logo
- Keylocks (with 2 keys + numbered locker key wrist strap)

Dimensions

W 400 mm / D 547 mm / H 2100 mm
 Height with skirting board 2170 mm

Optional upon request





CANB5W40FR-23


Single column locker with 5 doors in transparent polycarbonate


- Structure in 18 mm thick MFC panels
- Flammability and flame retardancy class B-s1, do (EN 13501-1)
- ABS edging with polyurethane glue
- Door in transparent polycarbonate 15 mm thick
- Adjustable feet
- Hinges certified for 80,000 opening and closing cycles
- Braked hinges
- Door opening angle 155°.
- Door number in resin-coated sticker with Fit Interiors logo
- Keylocks (with 2 keys + numbered locker key wrist strap)

Dimensions

W 400 mm / D 547 mm / H 2100 mm
 Height with skirting board 2170 mm

Optional upon request





CANB3W40FR-24V-23

Single column locker with 3 doors in transparent polycarbonate - LED inside

- Structure in 18 mm thick MFC panels
- Flammability and flame retardancy class B-s1, d0 (EN 13501-1)
- ABS edging with polyurethane glue
- Door in transparent polycarbonate 15 mm thick
- Adjustable feet
- Hinges certified for 80,000 opening and closing cycles
- Braked hinges
- Door opening angle 155°.
- Door number in resin-coated sticker with Fit Interiors logo
- Keylocks (with 2 keys + numbered locker key wrist strap)
- Trunking LED profile IP20 with power supply

Colour to be chosen among:

(C) 6000 K cold light

(N) 4000 K natural light


(W) 3000 K warm light


Dimensions

W 400 mm / D 547 mm / H 2100 mm

Height with skirting board 2170 mm

Optional upon request





CANB4W40FR-24V-23

Single column locker with 4 doors in transparent polycarbonate - LED inside

- Structure in 18 mm thick MFC panels
- Flammability and flame retardancy class B-s1, do (EN 13501-1)
- ABS edging with polyurethane glue
- Door in transparent polycarbonate 15 mm thick
- Adjustable feet
- Hinges certified for 80,000 opening and closing cycles
- Braked hinges
- Door opening angle 155°.
- Door number in resin-coated sticker with Fit Interiors logo
- Keylocks (with 2 keys + numbered locker key wrist strap)
- Trunking LED profile IP20 with power supply

Colour to be chosen among:

(C) 6000 K cold light

(N) 4000 K natural light

(W) 3000 K warm light


Dimensions

W 400 mm / D 547 mm / H 2100 mm

Height with skirting board 2170 mm

Optional upon request





CANB5W40FR-24V-23

Single column locker with 5 doors in transparent polycarbonate - LED inside

- Structure in 18 mm thick MFC panels
- Flammability and flame retardancy class B-s1, do (EN 13501-1)
- ABS edging with polyurethane glue
- Door in transparent polycarbonate 15 mm thick
- Adjustable feet
- Hinges certified for 80,000 opening and closing cycles
- Braked hinges
- Door opening angle 155°.
- Door number in resin-coated sticker with Fit Interiors logo
- Keylocks (with 2 keys + numbered locker key wrist strap)
- Trunking LED profile IP20 with power supply

Colour to be chosen among:

(C) 6000 K cold light

(N) 4000 K natural light

(W) 3000 K warm light

Dimensions

W 400 mm / D 547 mm / H 2100 mm

Height with skirting board 2170 mm

Optional upon request



Numbers



ACCRES1

Large resin-coated adhesive number, yellow and black

- With black Fit Interiors logo
- Replacing standard equipment

Dimensions

W 90 mm / H 90 mm



ACCRES2

Large resin-coated adhesive number, black and white

- With red Fit Interiors logo
- Replacing standard equipment

Dimensions

W 90 mm / H 90 mm



ACCRES3

Large resin-coated adhesive number, red and white

- With black Fit Interiors logo
- Replacing standard equipment

Dimensions

W 90 mm / H 90 mm



ACCNXT

Steel number, three-digit

- metal door plate
- three-digit numbering
- Fit Interiors logo
- sticker on back by ORAFOL mod. Aguard
- Replacing standard equipment

Dimensions

W 37 mm / D 2 mm / H 37 mm

Accessories



ACCUSB

Built-in USB socket

- 5V complete with power supply 100-240 V; 50-60 Hz - IP20

Locks

Mechanical combination lock



ACCHIAVE

Key lock

- 2 keys included plus numbered key fob
- Replacing standard equipment



ACCDKDI

Mechanical combination lock DIAL

- Brushed nickel color
- Replacing standard equipment



ACCCOMBI

Mechanical combination lock with handle

- Combi Lock
- Black colour
- Replacing standard equipment



ACCKEYLESS

Mechanical combination lock P1

- Satin nickel
- Replacing standard equipment



ACCKEYLESS1

Mechanical combination lock P1

- Satin gold
- Replacing standard equipment



ACCKEYLESS2

Mechanical combination lock P1

- Matte black
- Replacing standard equipment



ACCKEYLESS3

Mechanical combination lock P1

- Matte white
- Replacing standard equipment

Digital lock with battery



ACCASP6GNAR

Aspire 6G Narrow without handle

- Digilock digital lock 6G
- Brushed nickel color
- Replacing standard equipment



ACCASP6GNARWH

Aspire 6G Narrow with handle

- Digilock digital lock 6G
- Brushed nickel color
- Replacing standard equipment



ACCASP6GSTD

Aspire 6G Standard without handle

- Digilock digital lock 6G
- Brushed nickel color
- Replacing standard equipment



ACCASP6GSTDWH

Aspire 6G Standard with handle

- Digilock digital lock 6G
- Brushed nickel color
- Replacing standard equipment



ACCDKSO

Next Sola3 4G with handle

- Digilock digital/mechanical lock
- Brushed nickel color
- Replacing standard equipment

Digital lock with battery



ACCOJOCSMAG

OCS Smart Graphite without handle

- Dual technology: Bluetooth + keypad
- Graphite color
- Replacing standard equipment



ACCOJOCSMAGH

OCS Smart Graphite with handle

- Dual technology: Bluetooth + keypad
- Graphite color
- Replacing standard equipment



ACCOJOCSMAS

OCS Smart Silver without handle

- Dual technology: Bluetooth + keypad
- Silver color
- Replacing standard equipment



ACCOJOCSMASH

OCS Smart Silver with handle

- Dual technology: Bluetooth + keypad
- Silver color
- Replacing standard equipment



ACCOJOCSMAW

OCS Smart White without handle

- Dual technology: Bluetooth + keypad
- White color
- Replacing standard equipment



ACCOJOCSMAWH

OCS Smart White with handle

- Dual technology: Bluetooth + keypad
- White color
- Replacing standard equipment

Proximity lock



ACCOJPRO

OTS Basic

- Ojmar RFID lock
- With battery included
- Replacing standard equipment



ACCOJPROA

OTS Basic with signal booster

- Ojmar RFID lock
- signal booster
- with battery included
- replacing standard equipment



ACCOTS20

OTS 20

- Ojmar proximity lock
- RFID lock
- no cable
- no battery
- no maintenance
- black finish
- replacing standard equipment



ACCOTS20A

OTS 20 with signal booster

- Ojmar proximity lock
- signal booster
- RFID lock
- no cable
- no battery
- no maintenance
- black finish
- replacing standard equipment



ACCOTSPUL

OTS Pulse

- Ojmar proximity lock
- battery included
- black finish
- replacing standard equipment



ACCOTSPULA

OTS Pulse with signal booster

- Ojmar proximity lock
- signal booster
- battery included
- black finish
- replacing standard equipment

Proximity lock



ACCASPSTDRFID

Aspire Standard Body RFID with handle

- Digilock proximity lock
- black finish
- visual and acoustic indicators
- ambidextrous
- vertical body
- replacing standard equipment



ACCASPVERRFID

Aspire Narrow Body RFID with handle

- Digilock proximity lock
- black finish
- visual and acoustic indicators
- ambidextrous
- vertical body
- replacing standard equipment

Additions

Electrical parts and led sources are not suitable in presence of sensors, including sensor of movement



ACCTAM

Single side panel

- 18 mm thick MFC panels
- ABS edging with polyurethane glue

Dimensions

W 550 mm / H 2066 mm



ACCTAMD

Double side panel

- 18 mm thick MFC panels
- ABS edging with polyurethane glue

Dimensions

L 1100 mm / H 2066 mm



ACCTAMHS

Single side panel - flush to body

- 18 mm thick MFC panels
- ABS edging with polyurethane glue

Dimensions

W 550 mm / H 2072 mm



ACCTAMDHS

Double side panel - flush to body

- 18 mm thick MFC panels
- ABS edging with polyurethane glue

Dimensions

L 1100 mm / H 2072 mm



ACCTAMSP

Single side panel with mirror

- 18 mm thick MFC panels
- ABS edging with polyurethane glue
- mirror size 450×1972 mm

Dimensions

W 550 mm / H 2072 mm



ACCTAMSD

Double side panel with mirror

- 18 mm thick MFC panels
- ABS edging with polyurethane glue
- mirror size 1000×1972 mm

Dimensions

W 1100 mm / H 2072 mm



ACCTAMXL

Single side panel for lockers with top

- 18 mm thick MFC panels
- ABS edging with polyurethane glue

Dimensions

W 610 mm / H 2092 mm



ACCTAMDXL

Double side panel for lockers with top

- 18 mm thick MFC panels
- ABS edging with polyurethane glue

Dimensions

W 1220 mm / H 2092 mm

**ACCTAML-24V**

Single side panel with LED channel

- 18 mm thick MFC panels
- ABS edging with polyurethane glue
- LED IP20, color to be chosen among:
(C) 6000 K cold light
(N) 4000 K natural light
(W) 3000 K warm light

Dimensions

W 610 mm / H 2092 mm

**ACCTAMD-24V**

Double side panel with LED channel

- 18 mm thick MFC panels
- ABS edging with polyurethane glue
- LED IP20, color to be chosen among:
(C) 6000 K cold light
(N) 4000 K natural light
(W) 3000 K warm light

Dimensions

W 1220 mm / H 2092 mm

**SPACE1**

Single end side panel in laminate, rounded above and below

Dimensions

W 550 mm / D 118 mm / H 2070 mm

**SPACE2**

Rounded panel for internal corner in laminate

Dimensions

W 118 (+112) mm / D 118 (+112) mm / H 2070 mm

**SPACE3**

Rounded panel for external corner in laminate

Dimensions

W 550 mm / D 118 mm / H 2070 mm

**ACCVEL20**

Upper veil for locker, up to 200 mm H

- 18 mm thick MFC panels
- ABS edging with polyurethane glue

**ACCVEL50**

Upper veil for locker, from 200 to 500 mm H

- 18 mm thick MFC panels
- ABS edging with polyurethane glue

**ADELED-24V****Adhesive LED to put under the locker**

- LED IP20, color to be chosen among:
(C) 6000 K cold light
(N) 4000 K natural light
(W) 3000 K warm light

**ACCTOS****Single locker top**

- 18 mm thick MFC panels
- ABS edging with polyurethane glue
Projection 60 mm

**ACCTOP****Double locker top**

- 18 mm thick MFC panels
- ABS edging with polyurethane glue
Projection 60 mm

**ACCTSL-24V****Single locker top with integrated LED channel**

- 18 mm thick MFC panels
- ABS edging with polyurethane glue
- LED IP20, color to be chosen among:
(C) 6000 K cold light
(N) 4000 K natural light
(W) 3000 K warm light
- Projection 60 mm

**ACCTPL-24V****Double locker top with integrated LED channel**

- 18 mm thick MFC panels
- ABS edging with polyurethane glue
- LED IP20, color to be chosen among:
(C) 6000 K cold light
(N) 4000 K natural light
(W) 3000 K warm light
- Projection 60 mm

**ACCZARSG**

Skirting board in ABS for single locker, satin aluminum finish

- Adjustable feet 100 mm high
- Complete with mounting accessories

**ACCZARDG**

Skirting board in ABS for double locker, satin aluminum finish

- Adjustable feet 100 mm high
- Complete with mounting accessories

**ACCZARSB**

Skirting board in ABS for single locker, white finish

- Adjustable feet 100 mm high
- Complete with mounting accessories

**ACCZARDB**

Skirting board in ABS for double locker, white finish

- Adjustable feet 100 mm high
- Complete with mounting accessories

**ACCZARSN**

Skirting board in ABS for single locker, black finish

- Adjustable feet 100 mm high
- Complete with mounting accessories

**ACCZARDN**

Skirting board in ABS for double locker, black finish

- Adjustable feet 100 mm high
- Complete with mounting accessories

Finishes

Door

Polycarbonate



TRANSPARENT

Structure lockers



MATT BLACK WAX



WHITE WAX

Structure lockers (fire ritardant)



MATT BLACK WAX



WHITE WAX

follow us



**fit
interiors**

**furniture for gyms,
health and golf clubs,
spa&wellness, hotel,
medical and corporate**

visit www.fitinteriors.com